

013495541 \*\*Image available\*\*

WPI Acc No: 2000-667482/ 200065

Surface treatment of fluororesin material for coaxial cable involves  
irradiating fluororesin material placed inside a thin quartz tube  
immersed in aqueous solution containing ultraviolet absorption compound

Patent Assignee: INAGAKI K (INAG-I); NISSEI DENKI KK (NISS-N); SHIZUOKA KEN  
(SHIZ-N)

Number of Countries: 001 Number of Patents: 001

Patent Family:

Patent No	Kind	Date	Applicat No	Kind	Date	Week
JP 2000256488	A	20000919	JP 9961581	A	19990309	200065 B

Priority Applications (No Type Date): JP 9961581 A 19990309

Patent Details:

Patent No	Kind	Lan	Pg	Main IPC	Filing Notes
JP 2000256488	A		5	C08J-007/00	

Abstract (Basic): JP 2000256488 A

NOVELTY - One end of a thin quartz tube (3) is immersed in an aqueous liquid (2) containing ultraviolet absorption compound, and is filled with aqueous liquid by capillary action. A fluororesin material (F) is made to run inside the tube and an excimer laser light (L) is irradiated on the quartz tube.

USE - For coaxial cable manufacture.

ADVANTAGE - The adhesion and wettability of surface treated layer and the fluororesin material are improved. A favorable surface modification effect by continuous surface treatment and higher productivity are achieved.

DESCRIPTION OF DRAWING(S) - The figure shows sectional drawing of apparatus for surface treatment of fluororesin material.

Aqueous liquid containing ultraviolet absorption compound (2)

Quartz tube (3)

Fluororesin material (F)

Excimer laser (L)

pp; 5 DwgNo 1/1

Derwent Class: A14; A35; A85; P42

International Patent Class (Main): C08J-007/00

International Patent Class (Additional): B05D-003/06; B05D-003/10;  
B05D-007/20; C08L-027-12